



The Ultra HD 24/7 signage solution

Engage customers with ultra impactful professional signage – 24 hours a day, 7 days a week – with Toshiba's TD-U series. Ideal for those who need to show a continuous stream of high quality content, you can enjoy clarity and reliability with robust displays that won't let you down. What's more, with an optional integrated touch screen overlay, you're able to use interactive content to engage, entertain and inform your customers.

Capable of usage in landscape or portrait orientation, the displays can adapt to the environment you place them in. And the wide range of inputs (including RS232 and LAN control), scheduling features and control settings give you the flexibility to show what you want, when you want. You can even show up to four separate Full HD inputs simultaneously via split screen. The displays also give you the flexibility to show a wider range of content with the optional Intel® OPS slot. With a 4k, 3840 x 2160 resolution display, 178-degree viewing angle – and 500 cd/m² *(Nit) screen brightness – it's easy to see how Toshiba's TD-U series makes an impression.

TD-U series



85"

Features

- 500 cd/m²* Screen Brightness
- Reliable 24/7 Professional Signage
- Optional 6-point touchscreen
- RS232 and LAN Control
- Ultra HD 4K Display
- 178 degree viewing angle

		TD-U852	TD-U852TS
Screen	Diagonal Screen Size (cm/inch)	216cm/85"	216cm/85"
	Recommended Maximum Daily Usage (Hours)	24	24
	Backlight	Direct LED	Direct LED
	Bezel Width	21.2	23.2 (L/R) 21.9 (T/B)
	Portrait Mode	Yes	Yes
	Panel Resolution	3840 x 2160	3840 x 2160
	Viewing Angle (°)	178	178
	Brightness (cd/m ²)	500	450
	Native Contrast (number)	3000	2700
	Response Time (G to G) (ms)	6.5	6.5
UHD 4K (2160p)	Yes	Yes	
Inputs	HDMI	4	4
	HDMI Support Type	1.4b	1.4b
	DisplayPort	2	1
	DisplayPort Support Type	ver1.2	ver1.2
	Analogue D-SUB	1	1
	USB	-	Yes
	RS232	Yes	Yes
	LAN (Control)	Yes	Yes
	Remote Extender	Yes	Yes
Mini Jack (Audio)	Yes	Yes	
Supported Input Resolutions	HDMI	3840 x 2160	3840 x 2160
	DisplayPort	3840 x 2160	3840 x 2160
	VGA (D-Sub)	3840 x 2160	3840 x 2160
Outputs	RS232	1	1
	Remote	1	1
	Mini Jack (Audio)	1	1
	Speakers	10W + 10W	10W + 10W
Other Features	Touch Screen	–	Yes
	Touch Screen Number of Supported Points	–	6 Point
	OPS Slot	–	Yes
	No Signal Power Off	Yes	Yes
	Screen Saver	Yes	Yes
	Brightness Sensor	Yes	Yes
	Scheduler	Yes	Yes
	Picture Shift	Yes	Yes
QUAD FHD Splitscreen	Yes	Yes	
Panel Lock	Yes	Yes	
Power Supply	Input	AC 100-240 V, 50/60 Hz	AC 100-240 V, 50/60 Hz
	Active Consumption	575W	575W
	Energy Saving Consumption	410W	410W
	Standby Consumption	<0.5W	<0.5W
	Mains Plug Type	2 pin IEC mains leads	2 pin IEC mains leads
Dimensions	Width (mm)	1925.6	1925.6
	Width Bezel (mm)	21.2	23.2 (L/R) 21.9 (T/B)
	Height (mm)	1108.2	1108.2
	Depth (mm) - Maximum Point	104.7	116.8
	Weight (kg)	98	110.8
	Packed Width (mm)	2012	2012
	Packed Depth (mm)	294	294
	Packed Height (mm)	1296	1296
	Packed Weight (kg)	107.9	118.8
VESA - W x H (Screw Type)	500 x 400 + 500 x 600	500 x 400 + 500 x 600	